



Industrial Marine Architectural Coatings

TECHNICAL DATA SHEET

CODE: 29004

POLYMAR VARNISH

DESCRIPTION

POLYMAR VARNISH is a one-component, glossy, polyurethane marine varnish with fast drying and very good resistance to solar radiation.

RECOMMENDED USE

It is suitable for painting all surfaces above the waterline (wooden, metal, polyester). It contains UV filters that increase resistance to solar radiation. It also offers excellent spreadability.

PHYSICAL DATA

- **Shade:** Clear
- **Finish:** High gloss
- **Volume solids:** 45 % \pm 2
- **Specific gravity:** 1 – 1,2 Kg / Lt
- **Indicated dry film thickness:** Dry film 30 – 80 μ m
- **Theoretical spreading rate:** 10 – 12 m² / Lt
- **Drying time:**
 - **Dry to touch:** 2 hours at 23°C
 - **Recoat time:** Min time: 10 hours Max time: -

SURFACE PREPARATION

All surfaces to be painted must be free of grease, rust, and dust. On a prepared surface one or two coats.

APPLICATION DETAILS

- Stir well before use. The product is applied with a spray gun, airless and with a paint brush or paint roller for smaller surfaces.
- Dilution: up to 5% with solvent N'403 ή N'404.
- Tools cleaning: with solvent N'403.

SAFETY

Use the product to well ventilated place.
Wear suitable protective gloves, eyeglasses, and face protection.

The above information and our technical advice-whether verbal or in writing-are given in good faith and according to our tests. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses.